

A collection of various industrial push buttons and emergency stop buttons. The items include a large red emergency stop button with a yellow base, a yellow button with a black triangle symbol, a green button, a blue button, a red button, a button with a key symbol, and several smaller buttons in red, green, and white. The buttons are arranged on a white background.

KRAUS & NAIMER


The development of the Blue Line rotary switch, contactor and motor starter product ranges is based on more than seventy-five years experience by Kraus & Naimer in the design and manufacture of electrical switchgear. Kraus & Naimer pioneered the introduction of the cam operated rotary switch and continues to be recognized as the world leader in that product field.

BLUE LINE

Blue Line products are protected by numerous patents throughout the industrial world. They are built to national and international standards and designed to withstand adverse temperatures and climates.

Blue Line products are accepted and universally recognized for their quality and workmanship. They are supported by a worldwide sales and service organization.

The Kraus & Naimer Registered Trademark



WORLDWIDE SYMBOL
FOR QUALITY SWITCHGEAR

Contents	Page
Programs and Description	2, 3
Complete Standard Units	4, 5
Pre-assembled Front Elements	6, 7
Front Element Components	7, 8
Legend Plates	8, 9
Coupling Plate and Pilot Light Assemblies	9
Series Elements, Contact Blocks and Enclosures	10
Accessories	10-12
Front Plates for Push Buttons	13, 14
Front Plates for Mushroom Push Buttons	15
Color Caps for Pilot Lights	16
Design	17
Dimensions	18-21
Technical Data	22, 23
Blue Line Switchgear: Summary	24

Programs

Push Buttons and Pilot Lights, 22,5 mm Ø

Push buttons and pilot lights by Kraus & Naimer represent an ideal combination of functional security and economical efficiency in a modular design.

Push Buttons

- non-illuminated or illuminated
- flush, extended or with extended front ring
- momentary or latched (for converting into spring return function)

Pilot Lights

- Standard units flush or conical
- Solid pilot lights (direct wire)

Double-Push Buttons

- non-illuminated or illuminated

Emergency Stop Push Buttons

- fool-proof
- non-illuminated or illuminated
- without and with key
- optional mounting in enclosure

Potentiometer

- incl. resistor

Reset Push Buttons

- incl. reset rod

Rotary Switches

- non-illuminated or illuminated
- without and with key
- momentary (for converting into spring return function)

Cam Switches

- ON/OFF switches and double-throw switches
- protection IP 65
- for further cam switches, refer to Catalog 120

Enclosures

- plastic yellow or gray
- with 1, 2, 3, 4 or 6 positions

Legend Options

- front plates and color caps
- legend inserts

Accessories

- a wide range of accessories are available, e.g. protection shrouds and protection caps

Environmentally compatible Materials

- cadmium and asbestos-free
- recyclable

Selection

- complete units
- pre-assembled front elements
- individual components

Front
Element




Legend
Plate



Fixation
Ring



Coupling
Plate



Contact Blocks
LED Pilot Light
Assemblies



Front Elements

- ergonomical design, front rings metallic colored or black
- illuminated elements offer excellent brightest and contrast in all light conditions
- pilot lights with perfect light due to special lenses
- any inscription, abrasion-resistant by laser
- latched push buttons and rotary switches are convertible into spring return function
- mushroom push buttons with large points
- high protection and food resistance: push buttons and pilot lights IP 67/IP 69K, double-push buttons and rotary switches IP 66
- for special operating available with protection caps

Legend Plates

- for front elements and double-push buttons
- with legend inserts
- available with lasered or engraved inscription

Fixation Nut

- is part of the front element
- nut key for fixation nut as accessories

Coupling Plate

- for contact blocks and LED pilot light assemblies
- for max. 3 elements per contact level
- up to 6 contacts on 2 contact levels are possible

Contact Blocks and LED Pilot Light Assemblies

- finger-proof and open terminals (IP 20)
- captive mounting screws
- low overall depth, for mounting in commercial plaster depth box

Contact Blocks

- available as N/C and N/O
- high switching capacity, both in AC-15- and DC-13-operation (technical data see page 22)

LED Pilot Light Assemblies

- in green, red and white color
- long life (100 000 running hours) by especially low power consumption and vibration resistance
- with only 2 voltage ranges the worldwide common applications are covered
- for decoupled function control LED series elements are available

Program Completion

For extensive and complicated switching programs we recommend the use of cam switches size S00 described in Catalog 120. The design and appearance closely match the described push buttons and pilot lights.

Order Information

By changing the order text from P SN to P SB the unit will be specified with black front ring.


Description

Push Buttons and Pilot Lights, 22,5 mm Ø


The modular design of the series push buttons and pilot lights meets your personal requirements in every respect.

Front Elements

Push buttons non-illuminated



Push buttons illuminated



Mushroom push buttons



Rotary switches




Double-push buttons



Emergency stop push buttons



Pilot lights




Complete Standard Units

Solid pilot lights

available with flush or extended color cap



Contact Blocks and LED Pilot Light Assemblies



Potentiometer







incl. resistor








Cam switches



Complete Standard Units

Push Buttons Pilot Lights	Code	Rotary Switches Double-Push Buttons, Potentiometer	Code
Push buttons flush, IP 67/IP 69K non-illuminated		Rotary switches, IP 66 non-illuminated, latched (changeable by coding pieces to spring return function)	
 green  red  green I  red O 	P SN-WD0001 P SN-WD0002 P SN/D/G/X1-K10 P SN/D/R/X0-K01	 2 positions  3 positions 	P SN/WRK-K10 P SN/WRK3-K20
Pilot lights flush, IP 67/IP 69K with LED element		Double-push buttons, IP 66 with LED element, color cap opaque	
 green 12 V-30 V AC/DC red 12 V-30 V AC/DC green 85 V-264 V AC red 85 V-264 V AC	P SN-WD0003 P SN-WD0004 P SN-WD0005 P SN-WD0006	 85 V-264 V AC green I  red O 	P SN/DD/L/GR/X1-X0-K11
Solid pilot lights, IP 67/IP 69K for direct wire (without bulb), bulb holder BA 9s		Potentiometer, IP 66 3 separate screw terminals, $P_{max.} = 0,5 \text{ W}$	
flush  green red yellow blue opaque	P SN/LC/G P SN/LC/R P SN/LC/Y P SN/LC/B P SN/LC/W	 1 k Ω 4,7 k Ω 10 k Ω	P SN/R1K P SN/R4K7 P SN/R10K
extended (conical)  green red yellow blue opaque	P SN/LCH/G P SN/LCH/R P SN/LCH/Y P SN/LCH/B P SN/LCH/W	Other resistance values on request.	

Complete Standard Units

Emergency Stop Push Buttons	Code	Cam Switches	Code
Emergency stop push buttons, IP 66/IP 69K fool-proof acc. to ISO 13850/EN 418 reset by pulling complement max: 4 contact blocks  red  red 	P SN/PV-K01 P SN/PV-K11	Cam switches, IP 65 ON/OFF switches  1 pole  	CG4 A200-600 FS1 CG4 A290-600 FS1
reset by key operation 1 key, locking MS1  red 	P SN/PVS-K01	Double-throw switches  1 pole  2 pole	CG4 A210-600 FS1 CG4 A211-600 FS1
top yellow, bottom black reset by pulling complement max: 3 contact blocks  red  red 	P SN/PV-KC11-IY P SN/PV-KC02-IY	Double-throw switches with spring return to center  1 pole 	CG4 A214-600 FS1
foot and palm switch, IP 67/IP 69K top yellow, bottom black reset by pulling  red 	P FT/R-V-KC01-IY	Double-throw switches with electrically isolated contacts  1 pole 	CG4 A710-600 FS1
For further cam switches, refer to Catalog 120.			

Pre-assembled Front Elements

Push Buttons Pilot Lights		Code	Rotary Switches Double-Push Buttons		Code
	Push buttons, IP 67/IP 69K		Rotary switches, IP 66		
	flush, non-illuminated		switching angle 60°, latched ¹		
	green	P SN/D/G	2 positions, non-illuminated	↙	P SN/WRK
	red	P SN/D/R		↘	P SN/WKV
	green I	P SN/D/G/X1			
	red O	P SN/D/R/X0			
	flush, illuminated		3 positions, non-illuminated	↘↘	P SN/WRK3
	green	P SN/DL/G			
	red	P SN/DL/R			
	green I	P SN/DL/G/X1	2 positions, illuminated	↙	P SN/WRLK/G
	Push buttons, IP 67/IP 69K		green		P SN/WRLK/R
	extended, non-illuminated		red		P SN/WRLK/Y
	green	P SN/DH/G	yellow		P SN/WRLK/B
	red	P SN/DH/R	blue		P SN/WRLK/W
	extended, illuminated		opaque		
	green	P SN/DLH/G	3 positions, illuminated	↘↘	P SN/WRLK3/G
	red	P SN/DLH/R	green		P SN/WRLK3/R
			red		P SN/WRLK3/Y
			yellow		P SN/WRLK3/B
			blue		P SN/WRLK3/W
	Pilot lights, IP 67/IP 69K		Rotary switches, key operated, IP 66		
	flush		switching angle 60°, latched		
	green	P SN/L/G	1 key, locking MS1		
	red	P SN/L/R	2 positions		
	yellow	P SN/L/Y	key can be removed in O I	↙	P SN/WRS
	blue	P SN/L/B	key can be only removed in O	↘	P SN/WRS/A1
	opaque	P SN/L/W			
			3 positions		
			key can be removed in I O II	↘↘	P SN/WRS3
	Pilot lights, IP 67/IP 69K		key can be only removed in O	↘↘	P SN/WRS3/A1
	extended (conical)		Double-push buttons, IP 66		
	green	P SN/LH/G	color cap opaque		
	red	P SN/LH/R			
	yellow	P SN/LH/Y			
	blue	P SN/LH/B	green	I	P SN/DDL/GR
	opaque	P SN/LH/W	red	O	P SN/DDL/GR/X1-X0
			green	START	P SN/DDL/GR/GB1-GB0
			red	STOP	
			black	↑	P SN/DDL/S/X7-X7
			black	↓	

¹changeable by coding pieces to spring return function (40° switching angle)

Pre-assembled Front Elements

Front Element Components

Emergency Stop Push Buttons Reset Units	Code	Push Buttons Front Plates	Code
Emergency stop push buttons IP 67/IP 69K (turning) IP 66/IP 69K (pulling) fool-proof acc. to ISO 13 850/EN 418 complement max.: 4 contact blocks non-illuminated reset by pulling red reset by turning red  illuminated reset by pulling red reset by turning red  reset by key operation 1 key, locking MS1  red Reset units, IP 67/IP 69K non-illuminated  blue RESET blue R	P SN/PV P SN/PVT P SN/PVL P SN/PVLT P SN/PVS P SN/DZ/B/GB14 P SN/DZ/B/X6	Push buttons, IP 67/IP 69K without front plate with flush front ring, non-illuminated  momentary latched Push buttons, IP 67/IP 69K without front plate with extended front ring, non-illuminated  momentary Front plates, flush green red yellow blue white black legends see page 13  Front plates, extended green red yellow blue white black legends see page 13 	P SN/D/X P SN/DR/X P SN/DG/X P SN/XD/G P SN/XD/R P SN/XD/Y P SN/XD/B P SN/XD/W P SN/XD/S P SN/XDH/G P SN/XDH/R P SN/XDH/Y P SN/XDH/B P SN/XDH/W P SN/XDH/S

Front Element Components and Legend Plates

Mushroom Push Buttons Front Plates, Push Buttons		Code	Front Plates, Pilot Lights Color Caps, Emergency Stop Plates		Code
Mushroom push buttons, IP 67/IP 69K without front plate 	momentary	P SN/DP/G/X P SN/DP/R/X P SN/DP/Y/X P SN/DP/S/X	Front plates, flush 	green	P SN/XDL/G P SN/XDL/R P SN/XDL/Y P SN/XDL/B P SN/XDL/W
	green			red	
	red			yellow	
	yellow			blue	
Front plates 	black	P SN/DRP/G/X P SN/DRP/R/X P SN/DRP/Y/X P SN/DRP/S/X	Front plates, extended 	opaque	P SN/XDLH/G P SN/XDLH/R P SN/XDLH/Y P SN/XDLH/B P SN/XDLH/W
	latched			legends see page 14	
	green			green	
	red			red	
Push buttons, IP 67/IP 69K without front plate with flush front ring, illuminated 	yellow	P SN/XDP/G P SN/XDP/R P SN/XDP/Y P SN/XDP/W P SN/XDP/S	Pilot light, IP 67, IP 69K flush, without color cap 	blue	P SN/L/X
	white			opaque	
	black			legends see page 14	
	legends see page 15				
Push buttons, IP 67/IP 69K without front plate with extended front ring, illuminated 	momentary	P SN/DL/X P SN/DRL/X	Color caps 	green	P SN/XL/G P SN/XL/R P SN/XL/Y P SN/XL/B P SN/XL/W
	latched			red	
				yellow	
				blue	
Push buttons, IP 67/IP 69K without front plate with extended front ring, illuminated 		P SN/DGL/X	Emergency stop plates, IP 66 rectangular 	opaque	P SN/XZK/D99 P SN/XZK/GB99
				legends see page 16	
				33 mm x 50 mm	
				German	
Push buttons, IP 67/IP 69K without front plate with extended front ring, illuminated 		P SN/DGL/X	Emergency stop plates, IP 66 square, in four languages 	English	P SN/XYK1
				50 mm x 50 mm	

Legend Plates, Coupling Plate and Pilot Light Assemblies


Emergency Stop Plates Legend Carrier, Legend Insert	Code	Legend Plates, Coupling Plate LED Pilot Light Assemblies	Code
Emergency stop plates, IP 66 round, in four languages  Ø 90 mm Ø 60 mm	P SN/XAK1 P SN/XBK1	Legend plates, IP 66 complete standard unit  O I O I I O II STOP START Aus OFF Ein ON Störung FAULT Betrieb RUN HAND AUTO MAN. AUTO Aus Ein OFF ON HAND O AUTO MAN. O AUTO	P SB/ST/X88 P SB/ST/X89 P SB/ST/X93 P SB/ST/GB0 P SB/ST/GB1 P SB/ST/D5 P SB/ST/GB5 P SB/ST/D6 P SB/ST/GB6 P SB/ST/D8 P SB/ST/GB8 P SB/ST/D7 P SB/ST/GB7 P SB/ST/D11 P SB/ST/GB11 P SB/ST/D10 P SB/ST/GB10 P SB/ST/D12 P SB/ST/GB12
Legend carrier, IP 66 without plate  for push buttons	P SB/ST/X		
 for double-push buttons	P SB/STDD/X	Coupling plate 	P SN/A
Legend insert 	P SN/XST	LED pilot light assemblies front mounting  12 V-30 V AC/DC green red white ¹ 85 V-264 V AC green red white ¹	P SN/LED/G P SN/LED/R P SN/LED/W P SN/LED230/G P SN/LED230/R P SN/LED230/W
		base mounting  12 V-30 V AC/DC green red white ¹ 85 V-264 V AC green red white ¹	P SN/LEDC/G P SN/LEDC/R P SN/LEDC/W P SN/LEDC230/G P SN/LEDC230/R P SN/LEDC230/W

¹can be combined with blue, yellow or white pilot lights


Series Elements, Contact Blocks, Enclosures and Accessories

[illegible]

Accessories

Bulb Extractor Protection Caps	Code	Protective Shrouds Rod Link, Coding Pieces	Code
Bulb extractor 	P SN/LG	Protective shroud, IP 66 protection against accidental operation for push buttons and rotary switches (cannot be combined with legend plates) 	P SN/XGWK
Protection caps, IP 67 transparent, for aggravating environments (not in food areas) (cannot be combined with legend plates)  push buttons, flush pilot lights, flush	P SN/T/D	Protective shroud, IP 65 yellow, for emergency stop buttons (cannot be combined with legend plates) 	P SN/XGPV
 double-push buttons	P SN/T/DD	Rod link for operating the middle contact block of non- illuminated rotary switches with 3 positions 	P SN/XW
Protection cap prevents dirt and dust from getting into the keyhole (not food resistant)  rotary switches, key operated	P SN/XWS	Coding pieces for rotary switches to convert the latched function into spring return function (1 kit = 2 pieces) 	P SN/XC/Y

Accessories

Track Adapter Nut Key	Code	Fixation Nut Spare Key	Code
Track adapter for tracks acc. to EN 50 022 for front mounted units 	P SN/IVS	Fixation nut for push buttons, pilot lights and rotary switches 	P SN/GR
Nut key for push buttons, pilot lights and rotary switches 	P SN/MS	for cam switches 	S00 T170 10
for cam switches 	S00 T170 09	Spare key locking MS1 	P SN/ES/MS1

Front Plates for Push Buttons

Front Plates for Push Buttons non-illuminated				Code	Code
Color	Legend	Symbol	Meaning	Front Plates flush	Front Plates extended
black	Zu			P SN/XD/S/D2	P SN/XDH/S/D2
	Auf			P SN/XD/S/D3	P SN/XDH/S/D3
	Ab			P SN/XD/S/D4	P SN/XDH/S/D4
red	Aus			P SN/XD/R/D5	P SN/XDH/R/D5
black	Ein			P SN/XD/S/D6	P SN/XDH/S/D6
blue	Entsperren			P SN/XD/B/D14	P SN/XDH/B/D14
black	Vorwärts			P SN/XD/S/D15	P SN/XDH/S/D15
	Rückwärts			P SN/XD/S/D16	P SN/XDH/S/D16
	Heben			P SN/XD/S/D17	P SN/XDH/S/D17
	Senken			P SN/XD/S/D18	P SN/XDH/S/D18
red	STOP			P SN/XD/R/GB0	P SN/XDH/R/GB0
black	STOP			P SN/XD/S/GB0	P SN/XDH/S/GB0
green	START			P SN/XD/G/GB1	P SN/XDH/G/GB1
white	START			P SN/XD/W/GB1	P SN/XDH/W/GB1
black	CLOSE			P SN/XD/S/GB2	P SN/XDH/S/GB2
	UP			P SN/XD/S/GB3	P SN/XDH/S/GB3
	DOWN			P SN/XD/S/GB4	P SN/XDH/S/GB4
red	OFF			P SN/XD/R/GB5	P SN/XDH/R/GB5
black	ON			P SN/XD/S/GB6	P SN/XDH/S/GB6
	TEST			P SN/XD/S/GB9	P SN/XDH/S/GB9
blue	RESET			P SN/XD/B/GB14	P SN/XDH/B/GB14
black	FORWARD			P SN/XD/S/GB15	P SN/XDH/S/GB15
	REVERSE			P SN/XD/S/GB16	P SN/XDH/S/GB16
	RAISE			P SN/XD/S/GB17	P SN/XDH/S/GB17
	LOWER			P SN/XD/S/GB18	P SN/XDH/S/GB18
red		○	stop	P SN/XD/R/X0	P SN/XDH/R/X0
black		○		P SN/XD/S/X0	P SN/XDH/S/X0
green		I	start	P SN/XD/G/X1	P SN/XDH/G/X1
black		I		P SN/XD/S/X1	P SN/XDH/S/X1
white		I		P SN/XD/W/X1	P SN/XDH/W/X1
green		II		P SN/XD/G/X2	P SN/XDH/G/X2
black		II		P SN/XD/S/X2	P SN/XDH/S/X2
		+	increase	P SN/XD/S/X4	P SN/XDH/S/X4
		-	decrease	P SN/XD/S/X5	P SN/XDH/S/X5
blue		R	reset	P SN/XD/B/X6	P SN/XDH/B/X6
black		↑	guide motion	P SN/XD/S/X7	P SN/XDH/S/X7
		↖		P SN/XD/S/X8	P SN/XDH/S/X8
		✋	hand-control	P SN/XD/S/X9	P SN/XDH/S/X9
		⌚	automatic cycle	P SN/XD/S/X10	P SN/XDH/S/X10
		⊕	inching	P SN/XD/S/X11	P SN/XDH/S/X11
		↶	disengaging	P SN/XD/S/X12	P SN/XDH/S/X12
		↶↷	unlock	P SN/XD/S/X13	P SN/XDH/S/X13
		↶↷	tighten	P SN/XD/S/X14	P SN/XDH/S/X14
		↶↷↶	release	P SN/XD/S/X15	P SN/XDH/S/X15
		↶↷↶	liquid	P SN/XD/S/X16	P SN/XDH/S/X16
		📢	horn	P SN/XD/S/X17	P SN/XDH/S/X17

Front Plates for Push Buttons

Front Plates for Push Buttons illuminated				Code	Code		
Color	Legend	Symbol	Meaning	Front Plates flush	Front Plates extended		
opaque	Zu			P SN/XDL/W/D2	P SN/XDLH/W/D2		
	Auf			P SN/XDL/W/D3	P SN/XDLH/W/D3		
	Ab			P SN/XDL/W/D4	P SN/XDLH/W/D4		
red	Aus			P SN/XDL/R/D5	P SN/XDLH/R/D5		
opaque	Ein			P SN/XDL/W/D6	P SN/XDLH/W/D6		
blue	Entsperren			P SN/XDL/B/D14	P SN/XDLH/B/D14		
opaque	Vorwärts			P SN/XDL/W/D15	P SN/XDLH/W/D15		
	Rückwärts			P SN/XDL/W/D16	P SN/XDLH/W/D16		
	Heben			P SN/XDL/W/D17	P SN/XDLH/W/D17		
	Senken			P SN/XDL/W/D18	P SN/XDLH/W/D18		
red	STOP			P SN/XDL/R/GB0	P SN/XDLH/R/GB0		
opaque	STOP			P SN/XDL/W/GB0	P SN/XDLH/W/GB0		
green	START			P SN/XDL/G/GB1	P SN/XDLH/G/GB1		
opaque	START			P SN/XDL/W/GB1	P SN/XDLH/W/GB1		
	CLOSE			P SN/XDL/W/GB2	P SN/XDLH/W/GB2		
	UP			P SN/XDL/W/GB3	P SN/XDLH/W/GB3		
	DOWN			P SN/XDL/W/GB4	P SN/XDLH/W/GB4		
red	OFF			P SN/XDL/R/GB5	P SN/XDLH/R/GB5		
opaque	ON			P SN/XDL/W/GB6	P SN/XDLH/W/GB6		
	TEST			P SN/XDL/W/GB9	P SN/XDLH/W/GB9		
blue	RESET			P SN/XDL/B/GB14	P SN/XDLH/B/GB14		
opaque	FORWARD			P SN/XDL/W/GB15	P SN/XDLH/W/GB15		
	REVERSE			P SN/XDL/W/GB16	P SN/XDLH/W/GB16		
	RAISE			P SN/XDL/W/GB17	P SN/XDLH/W/GB17		
	LOWER			P SN/XDL/W/GB18	P SN/XDLH/W/GB18		
red				○	stop	P SN/XDL/R/X0	P SN/XDLH/R/X0
opaque				○		P SN/XDL/W/X0	P SN/XDLH/W/X0
green				I	start	P SN/XDL/G/X1	P SN/XDLH/G/X1
opaque				I		P SN/XDL/W/X1	P SN/XDLH/W/X1
green				II		P SN/XDL/G/X2	P SN/XDLH/G/X2
opaque		II	P SN/XDL/W/X2	P SN/XDLH/W/X2			
		+	increase	P SN/XDL/W/X4	P SN/XDLH/W/X4		
		-	decrease	P SN/XDL/W/X5	P SN/XDLH/W/X5		
		blue	R	reset	P SN/XDL/B/X6	P SN/XDLH/B/X6	
opaque		↑	guide motion	P SN/XDL/W/X7	P SN/XDLH/W/X7		
		↖		P SN/XDL/W/X8	P SN/XDLH/W/X8		
		✋	hand-control	P SN/XDL/W/X9	P SN/XDLH/W/X9		
		⌚	automatic cycle	P SN/XDL/W/X10	P SN/XDLH/W/X10		
		⊕	inching	P SN/XDL/W/X11	P SN/XDLH/W/X11		
		↕	disengaging	P SN/XDL/W/X12	P SN/XDLH/W/X12		
		↔	unlock	P SN/XDL/W/X13	P SN/XDLH/W/X13		
		⚙	tighten	P SN/XDL/W/X14	P SN/XDLH/W/X14		
		🔓	release	P SN/XDL/W/X15	P SN/XDLH/W/X15		
		🔧	liquid	P SN/XDL/W/X16	P SN/XDLH/W/X16		
		🔊	horn	P SN/XDL/W/X17	P SN/XDLH/W/X17		

Front Plates for Mushroom Push Buttons

Front Plates for Mushroom Push Buttons				Code
Color	Legend	Symbol	Meaning	
black	Zu			P SN/XDP/S/D2
	Auf			P SN/XDP/S/D3
	Ab			P SN/XDP/S/D4
red	Aus			P SN/XDP/R/D5
black	Ein			P SN/XDP/S/D6
	Vorwärts			P SN/XDP/S/D15
	Rückwärts			P SN/XDP/S/D16
	Heben			P SN/XDP/S/D17
	Senken			P SN/XDP/S/D18
red	STOP			P SN/XDP/R/GB0
black	STOP			P SN/XDP/S/GB0
green	START			P SN/XDP/G/GB1
white	START			P SN/XDP/W/GB1
black	CLOSE			P SN/XDP/S/GB2
	UP			P SN/XDP/S/GB3
	DOWN			P SN/XDP/S/GB4
red	OFF			P SN/XDP/R/GB5
black	ON			P SN/XDP/S/GB6
	TEST			P SN/XDP/S/GB9
	FORWARD			P SN/XDP/S/GB15
	REVERSE			P SN/XDP/S/GB16
	RAISE			P SN/XDP/S/GB17
	LOWER			P SN/XDP/S/GB18
red		○	stop	P SN/XDP/R/X0
black		○		P SN/XDP/S/X0
green		I	start	P SN/XDP/G/X1
black		I		P SN/XDP/S/X1
white		I		P SN/XDP/W/X1
green		II		P SN/XDP/G/X2
black		II	P SN/XDP/S/X2	
		+	increase	P SN/XDP/S/X4
		-	decrease	P SN/XDP/S/X5
		↑	guide motion	P SN/XDP/S/X7
		↖		P SN/XDP/S/X8
		✋	hand-control	P SN/XDP/S/X9
		⌚	automatic cycle	P SN/XDP/S/X10
		⊕	inching	P SN/XDP/S/X11
		↗	disengaging	P SN/XDP/S/X12
		↔	unlock	P SN/XDP/S/X13
		⚙	tighten	P SN/XDP/S/X14
		👉	release	P SN/XDP/S/X15
		👉	liquid	P SN/XDP/S/X16
		🔊	horn	P SN/XDP/S/X17

Color Caps for Pilot Lights


Color Caps for Pilot Lights flush				Code
Color	Legend	Symbol	Meaning	Front Plates flush
opaque	Zu			P SN/XL/W/D2
	Auf			P SN/XL/W/D3
	Ab			P SN/XL/W/D4
red	Aus			P SN/XL/R/D5
opaque	Ein			P SN/XL/W/D6
	Vorwärts			P SN/XL/W/D15
	Rückwärts			P SN/XL/W/D16
	Heben			P SN/XL/W/D17
	Senken			P SN/XL/W/D18
red	STOP			P SN/XL/R/GB0
opaque	STOP			P SN/XL/W/GB0
green	START			P SN/XL/G/GB1
opaque	START			P SN/XL/W/GB1
	CLOSE			P SN/XL/W/GB2
	UP			P SN/XL/W/GB3
	DOWN			P SN/XL/W/GB4
red	OFF			P SN/XL/R/GB5
opaque	ON			P SN/XL/W/GB6
	TEST			P SN/XL/W/GB9
	FORWARD			P SN/XL/W/GB15
	REVERSE			P SN/XL/W/GB16
	RAISE			P SN/XL/W/GB17
	LOWER			P SN/XL/W/GB18
red		○	stop	P SN/XL/R/X0
opaque		○		P SN/XL/W/X0
green		I	start	P SN/XL/G/X1
opaque		I		P SN/XL/W/X1
green		II		P SN/XL/G/X2
opaque		II		P SN/XL/W/X2
		+	increase	P SN/XL/W/X4
		-	decrease	P SN/XL/W/X5
		↑	guide motion	P SN/XL/W/X7
		↖		P SN/XL/W/X8
		✋	hand-control	P SN/XL/W/X9
		⌚	automatic cycle	P SN/XL/W/X10
		⊕	inching	P SN/XL/W/X11
		↕	disengaging	P SN/XL/W/X12
		↔	unlock	P SN/XL/W/X13
		↔	tighten	P SN/XL/W/X14
		↕	release	P SN/XL/W/X15
		🍷	liquid	P SN/XL/W/X16
		📢	horn	P SN/XL/W/X17

Design


Programming and Circuit Design

Programming for converting the latched function into spring return function

Push buttons



Rotary switches



P SN/XC/Y




P SN/XC/Y in B



P SN/XC/Y in A and B


Key cannot be removed in spring return position

Rod link for operating the middle contact block of non-illuminated rotary switches with 2 and 3 positions



LED resistor element


P SN/XLED60





P SN/XLED60	1x	2x	3x	4x	5x	6x	7x
$U_e \leq$	60 V	90 V	120 V	150 V	180 V	210 V	240 V

LED test element

P SN/XLED/T



P SN/XLED230/T



P SN/XLED230/T	1x	2x
$U_e \leq$	400 V AC	500 V AC




Dimensions

mm
inch


Operating and Indicator Devices, Push Buttons, Rotary Switches, Rotary Switches key operated, Pilot Lights, Push Buttons illuminated, Mushroom Push Buttons, Solid Pilot Lights, Emergency Stop Push Button, Potentiometer

Operating and indicator devices




Push buttons


P SN/D




P SN/DH




P SN/DG(L)



P SN/DD




Push buttons P SN/D
base mounting



Rotary switches


P SN/W(R)K...

P SN/W(R)LK...




Rotary switches key operated

P SN/WRS




Pilot lights

P SN/LH




P SN/L




Push buttons illuminated

P SN/DL




P SN/DLH




Mushroom push buttons

P SN/DP




Solid pilot lights

P SN/LC...



P SN/LCH...




Emergency stop push button

P SN/PV.

P SN/PVT.


P SN/PVL.

P SN/PVS




Potentiometer

P SN/R...K




Front Mounting


Fixing adapter P SN/A




Pilot lights and illuminated push buttons




Push buttons with P SN/K... Push buttons with P SN/LED... + P SN/XLED...




Track adapter



Foot and palm switches P FT/R-V-KC01-IY



Plastic enclosure




Type	Control positions	a	b	e	Cable entries
P SN/I (Y)1	1	72	42,6	58,5	2xM16 3xM20 2xM25
P SN/I2	2	120	85,6	106,5	2xM20 3xM20 2xM25
P SN/I3	3	153	118,6	139,5	2xM20 2xM25 4xM20
P SN/I4	4	186	151,6	172,5	2xM20 2xM25 4xM20
P SN/I6	6	252	217,6	238,5	2xM20 2xM25 4xM20


Legend Carrier

Legend carrier


P SB/ST




P SB/STDD




Mounting drilling with slot




Grid dimension acc. to IEC/EN 60947



Grid dimension for different combinations




Protection cap with legend carrier cannot be combined




Type	A ≥		B ≥	
	mm	inch	mm	inch
P SN/...(IEC/EN 60947)	30	1.18	50	1.97
P SN/...	30	1.18	40	1.57
P SN/D... + P SN/T/D	33	1.30	40	1.57
P SN/D(R)P...	38	1.50	40	1.57
P SN/PV...	38	1.50	40	1.57
P SN/PV(L...)(S...) + P SN/D...	33	1.30	40	1.57
P SN/DDL...	30	1.18	55	2.17
P SN/DDL... + P SN/T/DD	33	1.30	58	2.28
P SB/ST	30	1.18	50	1.97
P SB/STDD	30	1.18	75	2.95
P SN/XAK...	90	3.54	90	3.54
P SN/XZK...	33	1.30	52	2.05
P SN/XBK...	60	2.36	60	2.36
P SN/XYK...	50	1.97	50	1.97


Grid dimension for P SN/DD...



Grid dimension for P SN/DD... with protection cap P SN/T/DD




Protection cap and protection shroud with legend carrier cannot be combined




Dimensions mm inch

Blanking Plug, Protection Caps, Protective Shroud, Emergency Stop Plates, Cam Switches


Blanking plug
P SN/B




Protection cap
P SN/T/D




Protection cap
P SN/T/DD




Protective shroud
P SN/XGWK




P SN/XGPV




Protection cap
P SN/XWS




Emergency stop plates
P SN/XAK




P SN/XZK...




P SN/XBK...



P SN/XYK1



Cam switches



B	C	D	M
28	5	29,5	12,5
1.1	.2	1.16	.49
L 1 stage		L 2 stages	
38,5		50,5	
1.52		1.99	

Technical Data

			Contact Blocks	LED Elements	Push Buttons Mushroom P/B momentary	Double-Push Buttons	Rotary Switches Rotary Switches illuminated
General			IEC/EN 60947, VDE 0660				
Standards and requirements							
Mechanical life	operations	x 10 ⁶	5	—	5	0,2	0,1
Max. operating frequency		S/h	3600	—	3600	3600	2000
Operating force		N	≤ 5	—	≤ 5	≤ 5	—
Operating torque		Nm	≤ 0,8 (screw terminals)	≤ 0,8 (screw terminals)	—	—	≤ 0,3
Protection IEC/EN 60529			IP 20	IP 20	IP 67/IP 69K	IP 66	IP 66
Environmental resistance			humidity, constant, acc. to IEC 60068-2-78				
			humidity, cyclic, acc. to IEC 60068-2-30				
Ambient temperature	open	min./max.	°C	-25/+70	-25/+70 ¹	-25/+70	-25/+70
Mounting position			any	any	any	any	any
Shock withstand acc. to IEC 60068-2-27		g	> 30	> 30	> 30	> 30	> 30
Shock period 11 ms, 1/2 sinus wave							
Max. permissible wire gage							
single core	min.-max.	mm ²	0,75-2,5	0,75-2,5	—	—	—
stranded wire	min.-max.	mm ²	0,5-2,5	0,5-2,5	—	—	—
Current Paths							
Rated impulse withstand voltage U _{imp}		V	6000	6000	—	—	—
Rated insulation voltage U _i		V	500	500	—	—	—
Overtoltage category/			III/3	III/3	—	—	—
Pollution degree							
Control circuit reliability at							
24 V DC/5 mA	fault frequency H _F		< 10 ⁻⁷ , < 1 failure per 10 ⁷ operations				
5 V DC/1 mA	fault frequency H _F		< 5 x 10 ⁻⁶ , < 1 failure per 5 x 10 ⁶ operations				
Max. fuse size	characteristic	A gL/gG	10	—	—	—	—
Switching Capacity							
Rated operational current I _o							
AC-15							
115 V		A	6	—	—	—	—
230 V		A	6	—	—	—	—
400 V		A	4	—	—	—	—
500 V		A	2	—	—	—	—
DC-13							
24 V		A	3	—	—	—	—
42 V		A	1,7	—	—	—	—
60 V		A	1,2	—	—	—	—
110 V		A	0,8	—	—	—	—
220 V		A	0,3	—	—	—	—
Electrical life							
AC-15							
230 V/0,5 A	operations	x 10 ⁶	1,6	—	—	—	—
230 V/1,0 A	operations	x 10 ⁶	1,0	—	—	—	—
230 V/3,0 A	operations	x 10 ⁶	0,7	—	—	—	—
DC-13							
12 V/2,8 A	operations	x 10 ⁶	1,2	—	—	—	—
Approvals							
Technical data on request.			UL/CSA	UL/CSA	UL/CSA	UL/CSA	UL/CSA

¹> 200 V AC/60 Hz: -25/+55 °C

Technical Data

			Rotary Switches key operated	Potentiometer Solid Pilot Lights	Pilot Lights	Push Buttons Push Buttons, illuminated Mushroom P/B, latched	Emergency Stop Push Buttons
General							
Standards and requirements			IEC/EN 60947, VDE 0660				
Mechanical life	operations	$\times 10^6$	> 0,1			> 0,1	> 0,1
Max. operating frequency		S/h	100			1800	600
Operating force		N				≤ 5	≤ 50
Operating torque		Nm	$\leq 0,5$				
Protection acc. to IEC/EN 60529			IP 66	IP 66 (Potentiometer) IP 67/IP 69K (pilot light)	IP 67/IP 69K	IP 67/IP 69K	reset by turning IP 67/IP 69K reset by pulling IP 66/IP 69K
Environmental resistance			humidity, constant, acc. to IEC 60068-2-78 humidity, cyclic, acc. to IEC 60068-2-30				
Ambient temperature	open	min./max.	°C	-25/+70	-25/+70	-25/+70	-25/+70
Mounting position				any	any	any	any
Shock withstand acc. to IEC 60068-2-27			g	> 30	> 30	> 30	> 50
Shock period 11 ms, 1/2 sinus wave							
Max. permissible wire gage							
single core	min.-max.	mm ²		0,5-1,5			
stranded wire	min.-max.	mm ²		0,5-1,5			
Current Paths							
Rated impulse withstand voltage U_{imp}		V		4000			
Rated insulation voltage U_i		V		250			
Overvoltage category/ Pollution degree				III/3			
Approvals							
Technical data on request.			UL/CSA	UL/CSA	UL/CSA	UL/CSA	UL/CSA

Foot and Palm Switches latched

General							
Standards and requirements			IEC/EN 60947, VDE 0660				
Mechanical life	operations	$\times 10^6$	> 0,1				
Max. operating frequency		S/h	≤ 600				
Operating force		N	≤ 60				
Protection acc. to IEC/EN 60529			IP 67, IP 69K				
Environmental resistance			humidity, constant, acc. to IEC 60068-2-78 humidity, cyclic, acc. to IEC 60068-2-30				
Ambient temperature	min./max.	°C	-25/+40				
Mounting position			any				
Shock withstand acc. to IEC 60068-2-27		g	> 15				
Shock period 11 ms, 1/2 sinus wave							

Cam Switches CG4¹

General							
Standards and requirements			IEC/EN 60947, VDE 0660				
Rated impulse withstand voltage U_e ²		V	440				
Rated insulation voltage U_{imp} ²		V	4000				
Rated thermal current I_u/I_{th}		A	10				
Rated operational current I_e	AC-21A	A	10				
220 V-240 V	AC-15	A	2,5				
380 V-440 V	AC-15	A	1,5				
Max. fuse size gL/gG-characteristic		A	10				
Max. permissible wire gage							
single core or stranded wire		mm ²	2 x 1,5				
flexible wire		mm ²	2 x 1,5				
Approvals							
Technical data on request.			UL/CSA/GOST/CCC ³				

¹For further cam switches, refer to Catalog 120. ²Valid for lines with grounded common neutral termination, overvoltage category III, pollution degree 3.

³If this approval is required, please request when ordering.

The Range of “Blue Line” Switchgear

Technical literature covering the following products is available on request.

	Catalog Number
Main Switches and Main Switches with Emergency Function 16 A-1250 A Maintenance Switches 20 A-315 A Switch Disconnectors 20 A-315 A According to IEC 60947-3, EN 60947-3, VDE 0660 part 107, IEC 60204, EN 60204 and VDE 0113	500
CL Switches 10 A-20 A C, CA and CAD Switches 10 A-315 A and L Switches 350 A-2400 A C, CA and CAD switches are designed for universal application. They are recommended for instrument, isolator, double-throw and motor control. L switches are designed for load and off-load applications. They are used to switch resistive or low inductive loads.	100
Optional Extras and Enclosures The complete product line, a large number of optional extras is available, including door interlocks, push-pull devices, cylinder and padlock attachments, control and indicator devices, AC motor drives, as well as enclosures, both insulated and metal.	101
A and AD Switches 6 A-25 A A and AD switches have 4 contacts in each switching stage. These switches provide an extensive range of switch functions and require a minimum mounting depth. Up to 36 switching positions are possible, with availability of 48 contacts per 12 stage switch column.	110
CG, CH and CHR Switches 10 A-25 A Ultra compact CG, CH and CHR switches are ideally suited for control and instrumentation applications. CG switch terminals are “finger-proof”, according to VDE 0106. Terminals are conveniently accessible for wiring and are delivered open. All CG4 switches offer specially designed gold plated contacts or H-bridges with “cross-wire” contact systems, which facilitates their use in electronic circuitry and chemically aggressive environments.	120
DH, DHR, DK and DKR Switches 6 A-16 A DH, DHR, DK and DKR switches incorporate unique corrosion resistant contacts that permit operation on system voltage as low as 1 V. They have fully enclosed and protected contacts which can be operated either by rotary and/or lateral handle movement. D switches are used in calibration and semiconductor circuits. They are also used for relay and contactor control.	130
X Switches 80 A-630 A X switches can be applied for load, tap and gang switching duties. They incorporate 6 contacts in each switching stage. Their compact design provides a minimum length dimension for mounting purposes.	140
KG Switches 20 A-315 A and KH and KHR Switches 16 A-80 A KG, KH and KHR switches are excellent circuit interruptors. They have high through fault and fault making capacities and are especially designed for use as isolators and safety switches for machine tools, distribution panels and switchboards. KG ON/OFF switches offer unusually high dimensioned air and creepage distances between terminals which are designed for time saving “straight-line” wiring. ON/OFF switches are available with up to 8 poles and double-throw switches are available with up to 4 poles.	150
Contactors 16 A-115 A and Motor Starters 1,1 kW-55 kW These include control relays, motor contactors, two and four pole output contactors, heating contactors, thermal overload relays.	200
Push Buttons and Pilot Lights, 22,5 mm Ø A complete range of state-of-the-art push buttons and pilot lights represent an ideal combination of functional security and economical efficiency in a modular design.	302

SALES AND SERVICE ORGANIZATION

Australia

australian solenoid Φ co.pty. ltd.

379 Liverpool Road, ASHFIELD, N.S.W. 2131
P. O. Box 1093, ASHFIELD, N.S.W. 1800
Tel: +61 2 9797-7333, Fax: 0092
e-mail: sales@austrasol.com.au

Austria

austro solenoid Φ ges.m.b.h.

Schumanngasse 35, Postfach 431
A-1181 WIEN
Tel: +43 1 404 06, Fax: 404 06-190
e-mail: aso@krausnaimer.com

Belgium, Luxembourg

solenoid benelux Φ b. v.

Stationstraat 34
B-3070 KORTENBERG
Tel: +32 2 757-0141, Fax: 1640
e-mail: info@solenoid.be

Brazil

solenoid do brasil Φ ltda.

Avenida Berna 230
04774-020 SAO PAULO
Tel: +55 11 5524-1288, Fax: 5521-4659/9633
e-mail: knbrasil@krausnaimer.com.br

Canada

canadian solenoid Φ inc.

219 Connie Crescent, Unit 13A
CONCORD, Ontario, L4K 1L4
Tel: +1 905 738-1666, Fax: 9327
e-mail: cdnsolenoid@consol.on.ca

Chile

ASEA BROWN BOVERI S. A.
Vicuña Mackenna 1602, Casilla 3555
SANTIAGO DE CHILE
Tel: +56 2 544-7411, Fax: 7418

Cyprus

ELECTROMATIC CONSTRUCTIONS LTD.
72, Evagoras Pallikarides Str., CY-2235 LATSIA-Nicosia
P. O. Box 12630, CY-2251 LATSIA-Nicosia
Tel: +357 2 48 41 41, Fax: 48 57 47

Czech Republic

OBZOR, výrobní družstvo Zlín
Louky-Slanica 378
CZ-76413 ZLÍN
Tel: +420 57 7195-111/-153 (Techn. Supp.)
Fax: +420 57 7195-152/-138
e-mail: ots@obzor.cz

Denmark

C. THIIM A/S Ingeniørfirma
Transformervej 31
DK-2730 HERLEV
Tel: +45 44 85 80 00, Fax: 80 05
e-mail: thiim@thiim.com

Finland

suomen solenoid Φ oy

Karitie 7
FIN-01530 VANTAA
Tel: +358 9 825-4240, Fax: 42410
e-mail: etunimi.sukunimi@finsol.fi

France

solenoid france Φ s. a.

33, rue Bobillot
F-75013 PARIS
Tél: +33 1 58 40 80 80, Fax: 45 80 91 19
e-mail: sales@solfrance.fr

Germany

deutsche solenoid Φ vertriebs-gmbh

Wikingerstraße 20-28, D-76189 KARLSRUHE
Postfach 10 01 24, D-76231 KARLSRUHE
Tel: +49 721 59 88-0, Fax: 59 28 28
e-mail: desol@krausnaimer.com

Great Britain

u. k. solenoid Φ ltd.

115 London Road
NEWBURY/BERKSHIRE RG14 2AH
Tel: +44 1635 45991, Fax: 37807
e-mail: sales@uksol.co.uk

Greece

KALAMARAKIS-SAPOUNAS S. A.
Ionias & Neromilou Str., P. O. Box 46566
GR-13671 ACHARNES/ATHENS
Tel: +30 2 10 240-6000-6, Fax: 240-6007
e-mail: ksa@ksa.gr

Hungary

GANZ, Schalter- u. Gerätefabrik
X. Kőbányai út 41/c, Postfach 87
H-1475 BUDAPEST
Tel: +36 1 261-5479, Fax: 4685
e-mail: ganzkk@ganzkk.hu

Iceland

BRAEDURNIR ORMSSON EHF
Lágmúli 6-9, P. O. Box 8670
REYKJAVIK
Tel: +354 530-28 00, Fax: 28 10
e-mail: skuli@ormsson.is

Iran

RBS technische und kommerzielle
Beratungsgesellschaft mbH
Kohlriege 14
D-33758 SCHLOSS HOLTE
Tel: +49 5207 9111-0, Fax: 9111-59
e-mail: kontakt@rbs-gmbh.de

Republic of Ireland

irish solenoid Φ ltd.

Bay 145, Shannon Free Zone
SHANNON, Co. Clare
Tel: +353 61 704700, Fax: 471084
e-mail: salesirs@krausnaimer.ie

Italy

solenoid italia Φ s.r.l.

Via Terracini, 9
I-24047 TREVIGLIO (BG)
Tel: +39 0363-30 11 12, Fax: 30 21 13

Japan

solenoid japan Φ co. ltd.

Yoshiwada Building 2F
1-11-6 Hamamatsucho
Minato-Ku, TOKYO 105-0013
Tel: +81 3 3436-6151, Fax: 6325

Kuwait

AMMAR & PARTNERS ELECTRICAL CO.
P. O. Box 1871
13019 SAFAT
Tel: +965 483-0122/483-0133
Fax: +965 484-1818

Malaysia

INDUSTRIAL AUTOMATION (M) Sdn Bhd
30-3 & 30-4 Loke New Road
55200 KUALA LUMPUR
Tel: +60 3-9-2210511, Fax: 2222299
e-mail: inquiry@iasb.com.my

Mexico

ING. JAVIER CABALLERO B.
A. Gaviño 30, Satélite,
53100, Edo. de Mexico, MEXICO
Tel: +52 5555 62-7577, Fax: 0434
e-mail: j_caballero_b@infosel.net.mx

Netherlands

solenoid benelux Φ b. v.

Wegtersweg 38, Postbus 199
NL-7556 BR HENGLO (Ov.)
Tel: +31 74 291-9441, Fax: 8380
e-mail: info@solenoid.nl

New Zealand

new zealand solenoid Φ co. ltd.

42 Miramar Avenue, P. O. Box 15-009
WELLINGTON
Tel: +64 4 380-9888, Fax: 9877
e-mail: sales@nzsolenoid.co.nz

Norway

norsk solenoid Φ a/s

Hjalmar Brantings vei 8, P. O. Box 21, Økern
N-0508 OSLO
Tel: +47 22 64 44 20, Fax: 65 39 49
e-mail: nos@norsksol.no

Poland

ASTAT sp. z o.o.
ul. Dąbrowskiego 461
PL-60451 POZNAŃ
Tel: +48 61 848-8871/72, Fax: 8276
e-mail: info@astat.com.pl

Portugal

ELECTRICOL-DAMAS, FERREIRA & DAMASCENO, S. A.
Apartado 1083
P-2671-852 SANTO ANTÓNIO DOS CAVALEIROS
Tel: +351 21 989-8939, Fax: 988-6464

Kingdom of Saudi-Arabia

HAWA ELECTRIC PANEL BOARD FACTORY
Industrial Area, P. O. Box 1684
DAMMAM 31441
Tel: +966 3 847-2061, Fax: 2056

Singapore

solenoid singapore Φ pte. ltd.

115A, Commonwealth Drive
03-17/23
SINGAPORE 149 596
Tel: +65 6473-8166, Fax: 8643
e-mail: krausnaimer@singsol.com.sg

Slovenia

SCHRACK Energietechnik d.o.o.
Glavni trg 47
SI-2380 SLOVENJ GRADEC
Tel: +386 2 88 392 00, Fax: 434 71
e-mail: schrack.sg@schrack-energietechnik.si

Republic of South Africa

south african solenoid Φ co.pty. ltd.

7 Village Crescent, Linbro Village
Linbro Business Park, SANDTON 2065
P. O. Box 511, KELVIN 2054
Tel: +27 11 608-6060, Fax: 608-2874
e-mail: sales@sasolenoid.co.za

Spain

HAZEMEYER ESPAÑOLA S. A.
Crta. de Tiana s/n, Esq. N-2
BADALONA-BARCELONA
Tel: +34 93 389-4262, Fax: 384-3586
e-mail: heshaze@catworld.net

Sweden

skandinaviska solenoid Φ ab

Dr. Widerströms Gata 11, FRUÅNGEN
Box 42097, S-126 14 STOCKHOLM
Tel: +46 8 97 00 80, Fax: 97 87 33
e-mail: order@skansol.se

Switzerland

AWAG Elektrotechnik AG
Sandbühlstraße 2, Postfach
CH-8604 VOLKETSCHWIL
Tel: +41 1 908-1919, Fax: 1999
e-mail: info@awag.ch

Taiwan

NUWTEC ENTERPRISE Co Ltd
No. 301, Sec. 1, Nan Kang Road
TAIPEI 115, Taiwan, R. o. C.
Tel: +886 2 265-13279, Fax: 13264
e-mail: nathan.nuwtec@msa.hinet.net

Turkey

ÜNAL KARDEŞ ELEKTRİK GEREÇLERİ A. Ş.
Beşyol, Eski Londra Asfaltı-6
TR-34630 SEFAKÖY-İstanbul
Tel: +90 212 624-9204, Fax: 592-4810
e-mail: info@unal kardes.com.tr

USA

american solenoid Φ co. inc.

760 New Brunswick Road, P. O. Box 430
SOMERSET, NJ 08873
Tel: +1 732 560-1240, Fax: 8823
e-mail: amsol@krausnaimer-us.com

